

JVHS-EX POSITIVE DISPLACEMENT SPUR GEAR FLOW METER

Works extremely well under high pressure. Ideal for measuring oil, fuel, additives and chemicals in hazardous area rated environments, such as oil production platforms, land-based oil recovery sites, chemical processing plants & laboratories.



APPLICATIONS

Designed for use in systems rated up to 15,000 psi (1035 bar), the JVHS gear meters are durable, accurate, and safe in high pressure environments. The JVHS series all can be hydro tested to 1.5 times the working pressure rating.

The JVHS meters, constructed of 316 stainless steel with Inconel 718 bolts, come equipped with medium-pressure autoclave connections. These units are for use in high pressure hydraulic and fuel systems; in offshore chemical injection systems including methanol, corrosion and wax inhibitors; or in water treatment chemical-injection systems.

FEATURES

- Three flow ranges from 0.003 to 7.0 GPM
- Accuracy: up to 0.5% of reading
- Pressure rating up to 15,000 PSI (1035 bar)
- Bi-directional flow capabilities
- Non-intrusive sensors, panel mount displays, and electronic modules available

BENEFITS

Affordable & Accurate

This meter has the ability to maintain consistent accuracy despite changing viscosity conditions*, with accuracy of +0.5% of reading.

Rugged Construction

The JVHS's solid body construction is made of 316 stainless steel for corrosion resistance and durability.

Flexible

Meter may be used in applications requiring bi-directional flow, and can be hydro tested to 1.5x the working pressure rating.

Hazardous Environment Ready

A complete line of explosion-proof sensors and displays are available for the JVHS meters.

* For viscosities above 30cP.

TECHNICAL SPECIFICATIONS

Measuring Accuracy

± 0.5% over 10:1 turndown with 30cP fluid

Repeatability

± 0.1%

Flow Measuring Range

0.003 to 0.8 gpm

0.01 to 2.0 gpm

0.03 to 7.0 gpm

Maximum Operating Pressure

Up to 15,000 psi

Maximum Fluid Temperature

185° F

Ports

3/8" MP Autoclave

MATERIALS OF CONSTRUCTION

Body	316L Stainless Steel
Gears & Ball Bearings	Stainless Steel
O-Ring	PTFE (other options available)
Bolts	Inconel 718



MJ Systems, LLC
Authorized AW-Lake Representatives
TX - Off (281) 842-7600
LA - Off (225) 726-7114
www.mjsusa.com • sales@mjsusa.com



2440 W. Corporate Preserve Dr. #600, Oak Creek, WI 53154 | www.aw-lake.com

©2016 AW-Lake Company. All rights reserved. Doc ID: JVHSD516 REV 3.20

JVHS-EX POSITIVE DISPLACEMENT SPUR GEAR FLOW METER


Works extremely well under high pressure. Ideal for measuring oil, fuel, additives and chemicals in hazardous area rated environments, such as oil production platforms, land-based oil recovery sites, chemical processing plants & laboratories.

METER DATA

Meter Size	Flow Range (GPM)	Impulses/Gallons	Impulses/CC	Diameter (in)	Height (in)	Ports	Filtration (microns)	Pressure Rating	Weight (Lbs/Kg)
JVHS-12KG-(EX)*	0.003-0.8	53,000	14.0	3.75"	2.5"	3/8" med pressure Autoclave	30	15,000 psi	7.5 / 3.4
JVHS-20KG-(EX)*	0.01-2.0	15,900	4.2	3.75"	2.5"	3/8" med pressure Autoclave	30	15,000 psi	7.4 / 3.36
JVHS-30KG-(EX)*	0.03-7.0	6,600	1.7	3.75"	3.0"	3/8" med pressure Autoclave	30	15,000 psi	8.9 / 4.04

RECOMMENDED ELECTRONICS

Model	Sensor Type	Sensor Features
EX Meters		
HUB-40EX	Hazardous area rated sensor	cCSAus certified pulse output hall effect single sensor
HUB-41EX	Hazardous area rated sensor	ATEX and IECEx hazardous area certifications
RT-30EX	Hazardous area rated flow transmitter	cCSAus certified rate & total display, 4-20mA analog output, HART communication available
Non EX Meters		
FIP-XX	4-20 mA Output Sensor	
MAG-PB	Pulse Sensor - <i>No Amplifier Required</i>	
RT-30SD	Local flow rate transmitter	


MJ Systems, LLC
Authorized AW-Lake Representatives
 TX - Off (281) 842-7600
 LA - Off (225) 726-7114
www.mjsusa.com • sales@mjsusa.com

Products may be subject to change without notice - Contact factory for the most up-to-date product information.



2440 W. Corporate Preserve Dr. #600, Oak Creek, WI 53154 | www.aw-lake.com

©2016 AW-Lake Company. All rights reserved. Doc ID: JVHSD516 REV 3.20