

MICROFLOW - POSITIVE DISPLACEMENT GEAR METER

Ideal for flow measurement of low and medium viscosity fluids (solvents, polyurethanes, oils and other non-abrasive fluids) at very low flow rates, as in chemical injection.



APPLICATIONS

AW Gear Meters offers these spur gear positive displacement flow meters that are suitable for a variety of applications:

- Chemical injection skids
- Fuel & solvent measurement
- Liquid seal bead dispensing
- Cylinder position measurement
- Batching
- Low flow applications to 2 cc/min (0.0005 gal/min)

TECHNICAL SPECIFICATIONS

Measuring Accuracy

± 0.5% or better, 10:1, ≥30cP

Flow Measuring Range

0.0005 to 0.25 gal/min

Maximum Operating Pressure

5,000 psi

Maximum Fluid Temperature

Depends on sensor used, refer to sensor tech guide.

Repeatability

± 0.1%

NPT Female Ports

Bi-directional flow capability

Certifications

ATEX approved, non-sparking, CSA Class 1, Div. 1

BENEFITS

Accurate & Reliable

This meter has the ability to maintain consistent accuracy despite changing viscosity conditions, with accuracy of +0.5% of reading or better. Low friction gears and bearings allow for accurate measurement of low viscosity fluids, down to 1cP (custom calibration recommended).

Rugged Construction

This PD meter's solid construction of 316 stainless steel body and stainless steel gears & bearings stand up to the most rugged environments.

Flexible

Meter may be used in applications requiring bi-directional flow.

Simple to Install & Use

Installation is easy because there is no need for straight run piping upstream or downstream of the flow meter.

Certified

Sensors are available with ATEX non-sparking or CSA Class I, Div. 1.

MATERIALS OF CONSTRUCTION

Body	316 Stainless Steel
Gear & Ball Bearings	Stainless Steel
O-Ring	PTFE (other options available)
Shaft	420 C Stainless Steel

RECOMMENDED SENSORS

Model	Sensor Type	Sensor Features
EX Meters		
HUB-40-Ex	Hazardous area rated sensor	CSA/CUS certified pulse output hall effect single sensor
RT-30Ex	Hazardous area rated flow transmitter	Rate & local display with 4-20mA analog output
Non EX Meters		
FIP-xx	Meter mounted analog output sensor	3-wire analog output, current or voltage
MAG-xx	Hall effect single sensor	Frequency output with conduit connection
RT-30SD	Local flow rate transmitter	Rate & local display with 4-20mA analog output

MICROFLOW - POSITIVE DISPLACEMENT GEAR METER

Ideal for flow measurement of low and medium viscosity fluids (solvents, polyurethanes, oils and other non-abrasive fluids) at very low flow rates, as in chemical injection.

METER DATA

Meter Type	Range (gal/min)	Impulse/gallon	Impulse/cc	Diameter (inches)	Height (inches)	Weight (lbs)	Ports	Filtration (micron)	Pressure Rating (psi)
JVS-01UF-25-NPT	.0005-.25	151,300	40	3.3	2.2	4	1/4" NPT	<10	5000
JVS-01UF-25-NPT-EX	.0005-.25	151,300	40	3.3	2.2	4	1/4" NPT	<10	5000



MJ Systems, LLC
Authorized AW-Lake Representatives
502 N 8th St • La Porte, TX 77571
Off (281) 842-7600 • Fax (281) 842-7601
www.mjsusa.com • sales@mjsusa.com

* For more information, see the RT-30EX data sheet. Products may be subject to change without notice - Contact factory for the most up-to-date product information.



2440 W. Corporate Preserve Dr. #600, Oak Creek, WI 53154 | www.aw-lake.com

©2016 AW-Lake Company. All rights reserved. Doc ID: MICR0D516 REV 4.20